



股票代码:002881

全球领先的物联网终端及无线数据方案提供商


SLM756

2020_6
SLM756
V1.02

美格机密
Meig Confidential



M 1 0



	M 1 0
	0

--	--

--	--	--

M 1 0

M 1 0

pin#	pin name	Pad characteristics	Functional description
1	MIPI_DSI0_LANE3_N	AI, AO	

51	VBUS	PI	USB VBUS Voltage
52	KYPD_PWR_N	DI	Power on key
53	GND	GND	GND
54	RF_WIFI/BT	AI,AO	RF signal
55	GND	GND	GND
56	GND	GND	GND
57	PM_RESIN_N	DI	PMIC reset
58	GPIO7_I2C_SCL	DO;B-PD:nppukp	Configurable I/O I2C or GPIO
59	GPIO6_I2C_SDA	DO;B-PD:nppukp	Configurable I/O I2C or GPIO
60	GND	GND	GND
61	RF_GPS	AI	RF signal-GPS ANT
62	GND	GND	GND

63

87	GND	GND	GND
88	UIM1_DET_N	DI,B-PD:nppukp	Configurable I/O UIM1 removal detection
89	GPIO3	B-PD:nppukp	Configurable I/O
90	GPIO2	B-PD:nppukp	Configurable I/O
91	GPIO1	B-PD:nppukp	Configurable I/O
92	GPIO0	B-PD:nppukp	Configurable I/O
93	GND	GND	GND
94	VREG_L11_SDC	PO	PMIC output 2.95V
95	SDC2_SDCARD_DET		

122	MIPI_DSI0_LANE0_P	AI, AO	MIPI display serial interface 0 lane 0 positive
123	MIPI_DSI0_LANE1_N	AI, AO	MIPI display serial interface 0 lane 1 negative
124	MIPI_DSI0_LANE1_P	AI, AO	MIPI display serial interface 0 lane 1 positive
125	MIPI_DSI0_LANE2_N	AI, AO	MIPI display serial interface 0 lane 2 negative
126	MIPI_DSI0_LANE2_P	AI, AO	MIPI display serial interface 0 lane 2 positive
127	GPIO36	B-PD:nppukp	Configurable I/O

128

	-25	-	75	
	-40	-	90	

4.3

4.3

VBAT	3.4		4.2	V
VBUS	4	5	6	V
	2.5	2.8	-	V

4.4

4.4

1.8V

V _{IH}		1.17	-	-
V _{IL}		-	-	0.63
V _{OH}		1.35	-	-
V _{OL}		-	-	0.45

4.5SIM_VDD

4.5 SIM_VDD

V _o		-	3	-
		-	1.8	-
I _o		-	-	55

4.6 PWRKEY

4.6 PWRKEY

PWRKEY		1.4	-	-	V
		-	-	0.6	V
		2000			ms



4.7 VCOIN



4.7 VCOIN


VCOIN-IN	VCOIN	2	3	3.25	V
I _{RTC-IN}	VCOIN	-		8	uA
VCOIN-OUT	VCOIN	-	3	-	

		TD-S	-	-	3.0	mA
		CDMA	-	-	3.0	mA
		FDD			2.0	mA
		TDD			2.1	mA

TOP







美格机密
Meig Confidential

